

AUTO PAY STATION APS-BC-RL

The APS-BC-RL is an automatic ticket payment machine.

It can operate independently or as part of the IPS Parking system

Its metallic exterior cabinet in combination with an aluminum front panel offers resistance in time and functionality.

Its interior lining of stainless steel gives excellent durability and safety.

During payment transactions the device accepts all possible combinations of coins and banknotes.

It can give coin change in all values and a specific predetermined banknote value.

Thermal printer issues a receipt at the end of every transaction.



IPS Parking & Automation Systems

POLYKASTRO- KILKIS

+30 2343020307

www.carparking.gr

General specifications

- Power 230 V AC@ 50 Hz
- Consumption (Max) 190W + 150W Heating Device
- Operate temperature 0°C to + 45°C
- Height: 170 cm Width 88 Depth: 70 cm
- Weight: 140 Kgr

Functionality

- Reading barcode tickets & Rfid (optional).
- Payment of short-term parkers tickets.
- It cooperates with the Central Administration System. (IPS Central Point)
- Video playback during standby (optional)
- Intercom with a central point

Money management system

- Electronic coin system (Accepts all denominations of coins)
- Electronic banknote reader with counterfeit detection (Accepts all denominations of notes)
- Cashbox storage capacity up to 3000 coins.
- Cashbox storage capacity up to 600 banknotes.
- Automatic coin recycling capacity of 70 pieces per value.
- Additionally there are two electronic coin containers (hoppers) with auto-fill function and capacity of up to 400 pieces per value.
- Automatic banknote recycling.
(One predefined banknote denomination).

Electronic equipments

- Industrial embedded Pc controller.
- Motorized Barcode Ticket Reader.
- Motorized Barcode Ticket Validator (optional)
- Color display 5.7 inch (TFT) (optional 15 inch)
- 4 digital I/O inputs
- 4 digital relay contacts.
- Thermal printer 80mm width
- Release coins Button.
- Cancel transaction Button.
- Intercom device
- Heating device (optional).
- Surge protection (optional)
- UPS (optional)

Interior - exterior construction.

- Metal construction 2mm galvanize – painted with Ral 1021
(Optional any Ral color)
- Stainless steel 3mm interior lining.
- Aluminum Front plate in Ral 5010 or 7040
- Interior insulation. (Optional)
- Drawer with lock for hoppers filling.